







Product Line Summary

PRODUCT	SPECIFICATION	PRODUCT SUMMARY
 <p>12 34® Formula</p>	MIL-PRF-81309H	12 34® Formula is the most effective multi-use formulation on the market today. Its lubricating, penetrating, moisture displacing, and corrosion inhibiting properties are unsurpassed by any single product of its kind.
 <p>Technical Petrolatum</p>	VV-P-236A(2)	VV-P-236 is a light lubricating grease of superior quality, with excellent anti-rust and moisture-displacing properties.
 <p>Molybdenum Disulfide Petrolatum</p>	MIL-PRF-83483E	Molybdenum disulfide, with its excellent lubricity and high load capacity, is particularly suitable for use on aircraft spark plugs and threaded fasteners and fittings at temperatures below 800°F.
 <p>Graphite Petrolatum</p>	SAE-AMS-2518D	This compound is designed to be used safely in contact with austenitic corrosion-resistant steels, titanium, nickel, and cobalt alloys, and similar corrosion-resistant metals and alloys.
 <p>Zinc Dust Petrolatum</p>	A-A-59313	This compound is designed to prevent seizing during assembly and disassembly of threaded or unthreaded aluminum and aluminum alloy components. It also provides corrosion protection to metal surfaces.
 <p>Boeing Anti-Seize Compound</p>	BMS3-28A	Armite's lead-free anti-seize per Boeing spec BMS3-28A can be used up to 350°F for threaded parts in contact with aluminum and magnesium alloys. Armite Lubricants is the only approved manufacturer to produce this spec material for The Boeing Company. Armite has been an approved supplier since 1988.
 <p>MIL907</p>	Formerly qualified to MIL-PRF-907F	Armite's MIL907 is ideal for use on threads of steel nuts, studs, bolts, and other mating surfaces, including superheated steam installations, at temperatures from -350° F to 2987°F (-212°C to 1641°C)
<p>1001 Penetrant</p>	MIL-PRF-680B Type II	Our 1001 Rust Penetrant is a hydrocarbon-based solvent and is used as detergent and cleaner for painted and unpainted metal parts.



Product Line Summary

PRODUCT	SPECIFICATION	PRODUCT SUMMARY
 LP-250	Commercial	LP-250 prevents seizing or galling at temperatures ranging from -350°F to 2987°F (-212°C to 1641°C). LP-250 is particularly useful for materials which gall easily, such as aluminum and stainless.
 LP-250F	Commercial	LP-250F is substituted for LP-250 if fitting tolerances are too liberal or if the high pressure fitting threads are coarse.
 No. 609	Commercial	Armite No. 609 is an excellent compound for sealing and protecting gaskets, spline assemblies, shafts, and all metal to metal surfaces. No. 609 assures easy disassembly, saving you costly down time and maintenance expenses.
 ZP-770	Commercial	Armite's ZP-770 is an anti-seize compound formulated from zinc powder, specialty oils, and grease for use on aluminum fasteners. ZP-770 helps reduce repair times when applied at every service interval. It is an excellent anti-seize in harsh environments.
 CP-2000	Commercial	Armite's CP-2000 offers protection against seizing, galling, and corrosion for all kinds of steel, except stainless. As a highly conductive metal, this copper based anti-seize is a go-to for electricians.
 AASC-M-2	Commercial	AASC-M-2 is designed for use on the threads of automotive engine spark plugs and in other applications involving high temperatures. However, because of its insulating properties, it should not be used where mating parts are required to be in good electrical contact.